



an EnerSys® company

Cordex® HP 1.2kW

48VDC Modular Switched Mode Rectifier



- High performance compact 25A rectifier for 48VDC telecom application
- 93.9% efficiency for reduced OPEX and carbon footprint
- Extended temperature range (-40 to 80°C) enabling to deliver full rated output power up to 65°C for installation in harsh outdoor and indoor environments
- 1RU x 2RU footprint for multiple mounting options
- High power density (21.8W/in³) yields more space for revenue generating equipment
- Wide AC input range for a variety of global installation requirements

Cordex® High-Performance rectifiers make a proven, reliable platform even better, with significant advancements in efficiency and performance.

In a compact, fan-cooled design, HP rectifiers open the possibility to wider ranges of applications and immediate OPEX/CAPEX savings, reducing total cost of ownership and impact on the environment.

The Cordex® HP 1.2kW is a perfect solution for small 48VDC power applications such as customer premise, xDSL, FTTx, distributed node B, and microwave. With a high operating efficiency and high temperature operation, CXC HP series rectifiers are also ideal for harsh outside plant enclosure installations.

Local and remote setup, adjustment and control is a simple single-step process with Cordex® CXC HP system controllers. By utilizing TCP/IP technology, complete configuration and monitoring of power equipment is possible through a network web browser.

Cordex® CXRF-HP 1.2kW Modular Switched Mode Rectifier

P/N: 010-619-20

Electrical	
Input Voltage:	Nominal: 176 to 276VAC Extended (high): 277 to 300VAC (de-rated power factor) Extended (low): 90 to 175VAC (de-rated output power)
Input Current:	Nominal: 7.4A max 90 to 132VAC: 6A max Input frequency: 45 to 70Hz
Power Factor:	>99%
THD:	<5% @ nominal input voltage
Efficiency:	93.9%
Output Voltage:	42 to 58VDC
Output Power:	Nominal AC Input: 1200W 110 to 132VAC: 600W (de-rated linearly to 491W @ 90VAC)
Output Current:	Nominal AC Input: 22.2A @ 54V (25A max @ 48V) 110 to 132VAC: 12.5A max (de-rated linearly to 10.2A @ 90VAC)
Load Regulation:	Static: <±0.5% Dynamic: <±1% for 40 to 90 to 40% load step, 2ms recovery time
Line Regulation:	Static: <±0.1% Dynamic: <±1% for any change within rated limits
Wide Band Noise:	<30mVrms <150mVp-p
Psophometric Noise:	<2mV
Performance / Features	
Indicators:	<ul style="list-style-type: none"> AC mains OK — green LED DC output OK — green LED Module alarm — red LED
Cooling:	Fan cooled
Adjustments (Via CXC HP Controller):	<ul style="list-style-type: none"> Float and equalize voltage Battery test voltage High and low voltage alarms high voltage shutdown Current limit Start delay time Slope %
Protection:	<ul style="list-style-type: none"> Current limit/short circuit Input/output fuses Output high voltage shutdown Output power limiting Thermal foldback/shutdown Input transient AC low line foldback/shutdown AC high voltage shutdown

Mechanical	
Dimensions:	mm: 41.4H x 84.8W x 256.8D inches: 1.63H x 3.34W x 10.11D
Weight:	1.23kg (2.7lbs)
Environmental	
Temperature:	Operating: -40 to 80°C (-40 to 176°F); full rated output up to 65°C (149°F) Storage: -40 to 85°C (-40 to 185°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	-500 to 3000m (-1640 to 9840ft)
Heat Dissipation:	<308 BTU per hour/90 Watts
Agency Compliance	
Safety:	<ul style="list-style-type: none"> CSA C22.2 No 60950-1-03 CE marked
EMC:	ETSI 300 386 Emissions: <ul style="list-style-type: none"> CFR47 (FCC) Part 15 Class B ICES-03 Class B EN55022 (CISPR 22) Class B C-tick (Australia) EN 61000-3-2, 3-3 Immunity: <ul style="list-style-type: none"> EN 61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-11 ANSI/IEEE C62.41 Cat B3
NEBS/Telcordia:	<ul style="list-style-type: none"> GR-1089-CORE GR-63-CORE



an EnerSys® company

Alpha Technologies Services, Inc. USA: 3767 Alpha Way, Bellingham, WA 98226 Canada: 7700 Riverfront Gate, Burnaby, BC V5J 5M4
Toll Free North America: +1 800 322 5742 Outside US: +1 360 647 2360 Technical Support: +1 800 863 3364
For more information visit www.alpha.com

© 2020 Alpha Technologies Services, Inc. All Rights Reserved. Trademarks and logos are the property of Alpha Technologies Services, Inc. and its affiliates unless otherwise noted. Subject to revisions without prior notice. E. & O.E.

08/2020
#048-738-10 REV I